

## Salt City Racing Superstock Rules 2024

### Frame

1. Factory production complete full parallel American passenger car frames only
2. No weight penalty on stock stub
  - a. fabricated frames must add 150 lbs. in front of the motor plate.
3. Must be full and complete on both sides
4. No part of the frame may be lower than four (4") inches from the ground except front cross member
5. 102 "minimum wheelbase. Except 101 wheelbase Camaro with stock suspension (strut type or coil over) will be allowed
6. Top tubular A-Arms are allowed
7. Tube type lower A Frames are allowed if they are stock dimensions
8. Unibody frames may be tied together from front firewall to rear kickup
9. Kickups from rear end to rear bumper optional
10. All cars must have a front & rear hook-up device such as a loop or chain to assist wreckers
11. No mirrors

### Roll Cage

Round steel tubing, seamless roll-over bars are required for the basic roll cage.

- a. Acceptable minimum size tubing is as follows: one and three-quarters ( $1 \frac{3}{4}$ ) inches by 0.090 of an inch or one and one-half ( $1 \frac{1}{2}$ ) inches by 0.095 of an inch for mild steel and DOM tubing - one and three-quarters ( $1 \frac{3}{4}$ ) inches by 0.083 of an inch for chrome-moly tubing). Aluminum and/or other soft metals are not allowed. Roll bar connections must be properly welded. Roll bar installation and workmanship must be acceptable to track officials.

Must be frame-mounted in at least six places.

1. Must consist of a configuration of front and rear hoops connected by tubing on the sides or side hoops.
2. Roll cage must be 3 inches or more above the driver's head with helmet on and strapped in seat.
3. Must have a minimum of one cross bar in the top halo of the roll cage.
4. Must have a bar across the back of the engine with vertical bars and rub rails, or similar protection.
5. No brace bars forward of the cage may be higher than stock hood height.
6. Main cage no further forward than engine plate.

## Door Bars

1. A minimum of three driver side door bars, at least 1.5-inch O.D., must be as parallel with the ground as possible and located perpendicular to the driver to provide maximum protection for driver, but without causing undue difficulty in getting into or out of vehicle.
2. The side bars must be welded to the front and rear of the roll cage members
3. Must have at least one cross door bar, minimum 1.25-inch O.D. on the passenger side of the car, either horizontal or angled.
4. A minimum of 18-gauge steel door plates welded from 'A' post to 'B' post top to bottom of the door bars will be required.

## Body

1. Bodies are expected to resemble stock OEM bodies or late model type race cars.
2. Fiberglass roofs and hoods are allowed.
3. Steel or aluminum bodies.
4. Rear Quarter Panels cannot extend in or out of doors.
5. Aftermarket nose pieces are allowed.
  - a. May not extend outside of the tires (82" max).
6. Floor pan thickness must be 1/8" metal minimum.
7. 6.5" rear spoiler max, spoiler supports may not extend above or beyond spoiler.
8. Max of 4 supports may be used. Maximum spoiler side height is 6.5". Max spoiler side length 18.5". Spoiler side front height 4"
9. Must have a minimum of 3 bars in front of driver-screen is optional
10. Sail panels must be of matching design with matching styles on both sides of the racecar.
  - a. Sail panels may have a maximum bow of four (4) inches top to bottom, maximum bow of three (3) inches front to back and may be no more than eight (8) inches above the back edge of deck.
  - b. Stock body deck height 43"
  - c. Late model body deck height 39"
  - d. Station wagons are allowed with no roof rake, no spoilers or wicker bills on the roof and cannot have full sail panels. They must be open.
  - e. On Late model style bodies. Roof length size minimum of 44" maximum of 54". Roof width size minimum of 48" maximum of 52" Roof must be flat side to side (no Rake) and can have maximum of 4" rake front to back.

## Suspension

1. 2 or 3 link suspension allowed
2. Stock 4 link suspension is allowed
3. Shocks do not have to be in stock location

4. Weight jacks are allowed
5. Must be leaf or coil spring, cannot be both
6. All suspension parts must be visible on both ends
7. No torque arms allowed except factory Camaro
8. Pull bar must be solid

## **Safety**

1. Helmets are required and must be a minimum of SA 2015
2. with certification label inside helmet
3. SFI approved flame/fire retardant fire suits, gloves and shoes are mandatory
4. An approved head/neck restraint system is mandatory (Hans, G-force, Hutchens or SFI rated neck collar)
5. Seat belts and shoulder harness cannot be more than three years old
6. The date of manufacture should always remain visible
7. A lever-type quick release latch must be fastened to the lap belt
8. All seat belts and shoulder harnesses must connect at the lap belt with a quick release buckle acceptable to series officials
9. Only custom manufactured racing aluminum seats acceptable to officials
10. All seats are required to have a head rest on the right side
11. All belts must be a minimum of two (2) inches wide
12. Belts must be bolted to the roll cage with no less than 3/8inch bolt
13. A center, crotch belt must be securely mounted to the lower seat frame at the bottom and to the lap seat belt on the top
14. Where the belts pass through the seat edges, it must have a grommet installed, be rolled, and/or padded to prevent cutting of the belt
15. Window nets are mandatory
16. The windshield must have three (3) bars in front of the driver.
17. No cell phones, or radios in car except for Raceceiver one way listening device set to

## **Fuel accessories & Fuel**

1. Fuel cells mandatory
2. Must have screw on cap
3. Must be set in steel box with minimum 2-inch steel straps
4. No electric fuel pumps
5. Racing gas or Alcohol only
6. No nitrous oxide
7. No pressure fuel systems

8. If the fuel cell does not have an aircraft style positive seal filler neck/cap system, a flapper, spring or ball type rollover valve is required.

### **Engine Option 1**

1. Max 410 cubic inch allowed.
2. No aluminum blocks or heads allowed.
3. No angle milling allowed.
4. Roller cams allowed.
5. Port and Polish allowed.
6. No magnetos allowed.
7. 23-degree heads only.
8. No dry sump systems allowed.
9. No titanium engine parts allowed, except valve retainers.
10. Steel rods only.
11. Headers with collectors pointed down or rear mandatory.
12. One 2 barrel or one 4-barrel carburetor; 2 throttle return springs are mandatory
13. Engines may be no further rearward than 4 inches from the #1 spark plug hole aligning with the centerline or the upper ball joint.

### **Engine Option 2 LS engines**

1. 383 Ci max
2. Any iron 4.8/5.3 Or 6.0 block is allowed no aluminum blocks
3. Must be DISH or FLAT, no dome pistons. Can be fly cut for valve clearance.
4. Any Factory Cathedral port head is legal. No aftermarket heads.  
(706,862,241,853,243,799,317,035,933,873) Port/ Polish ok
5. The car must display what engine package it is running with LS or SBC or SBF on the A pillar.
6. Valvetrain: Hydraulic roller cam only, stock rocker arms only, Beehive valve springs only
7. Ignition MSD 6010,6012,6014
8. 7800 RPM MAX

### **Engine Option number 3 – Crate Engine**

- Crate Engine - GM Performance Parts (GPP) factory-sealed CT400 Chevy small block crate engine (Part No. 88958604 or 88869602).
- Must be unaltered and sealed from factory at appropriate points (Intake, head, timing chain cover and oil pan) with approved GPP break-off bolts. "Only" GM Performance Crate Motor Specs will be followed during technical inspections. Any altered, damaged or missing GPP break-off bolts will result in driver being disqualified from that event

- May utilize one (1) Holley 4-barrel carburetor. Use of a spacer between carburetor and intake is optional but must be no more than 1-inch thick if used and may not be throttle bore adjustable. Aerosol carburetors are not permitted.
- Must utilize a maximum 6800 RPM rev limiter. (Rev Limit may be subject to changes if needed) Rev Limiter may not be within reach of the driver while in cockpit and must be easily accessible to Officials at any time.

10. FUEL gas or alcohol

11. Carbureted only – no fuel injection. Belt driven or mechanical pump ok. No electric fuel pumps!

12. Ignition: Flat timing curve from 2500-7800 mandatory

13. The engine must be a minimum of 82" from the back of the block to the center of the rear end. For LS engine **battery**

1. Must be securely mounted and covered
2. Must be fully enclosed if in cockpit
3. 12 volt only

### **Transmission & Driveshaft**

1. Any manual four speed or standard three speed with full gears including reverse.
2. Racing Transmissions Allowed: Bert, Brinn, Falcon
3. The driveshaft must be steel and painted white.
4. Minimum driveshaft diameter is 2 inches.
5. At least one driveshaft hoop made of at least ¼"x 2" steel and securely mounted to frame, cross member or floor pan.
6. No ball splines allowed.

### **Flywheel & Clutch**

1. No buttons
2. Multi- disc clutches are allowed
3. Must have a steel scatter shield.
4. If you have internal clutch transmission you may run aluminum bell housing. Example. Bert. Brinn Falcon

### **Gauges/Electronics**

1. All cars must use a max 7800 RPM rev limiter chip unless otherwise noted.

- a. This may be accomplished by using one, non-adjustable 12-volt ignition box with one high end rev limiter setting or an internal setting inside the box.
  - b. No additional ignition accessories are allowed.
  - c. All components must be out of driver reach, but accessible for inspection.
  - d. No magnetos or crank triggers are allowed.
2. No transmitting or listening devices in car
  3. No electronic monitoring computer devices capable of storing or transmitting information except tachometers allowed on car
  4. Digital tach allowed
  5. One 12volt ignition box allowed; must be located outside of cockpit in front of driver
  6. No timing retard controls allowed
  7. No traction control devices
  8. Any car suspected of running a traction control device due to unusual handling characteristics can be pulled out of competition and not allowed to race
  9. No bundling of wires, all wires must be open and visible

## **Differentials**

1. Any passenger or half ton pickup rear end is allowed
2. Floater rear ends are allowed
3. QC Rear Ends are allowed

## **Brakes**

1. Four-wheel brakes must be in working condition at all times.
2. Adjustable brakes are allowed
3. No scalloped rotors allowed
4. No aluminum or titanium calipers
5. No aluminum or titanium rotors

## **Wheels & Tires**

1. Steel wheels only
2. Bead locks allowed on right side only
3. No bleeder valves allowed
4. 10-inch wheel max
5. Absolutely no weight may be added to the wheels in any fashion.

6. Grooving and siping allowed.
7. Wheel covers are permitted on right side wheels only (5 fastener types recommended).
  - a. Inner mud plugs are permitted.
  - b. All mud covers must display car number on at least one side
  - c. Aluminum wheel spacers only allowed

Tires – Hoosier 500 (8 or 10”, Tire must match wheel width) PN’s 36103, 36105, 36108. Hoosier G-60 or American Racer KK-704. Asphalt Takeoffs (must durometer a min of 40 hot or cold) No chemical softening allowed. Grooving and/or siping is permitted. Hoosier F15 allowed on LR only.

### **Steering**

1. Quick release style.
2. Steering box location optional.
3. Rack and pinion allowed.

### **Shocks & Springs**

1. One steel non-adjustable shock per wheel.
  - a. No threaded body shocks.
2. No coil-overs, air or remote reservoir shocks.
3. Steel leaf springs only allowed.
4. One coil and/or leaf spring per wheel only.
5. No external or internal bumpers or stops allowed.
6. One steel, non-progressive, closed end spring per wheel only allowed.
  - a. All coil springs must be a minimum 4.5 OD.
  - b. Front coil springs must be 9.5” free height with 0.5” tolerance.
  - c. The rear coil must be 11”-20” free height with 0.5” tolerance.

### **Weight**

1. Engine Option 1: 2600 lbs.
2. Engine Option 2: 2600 lbs.
3. All bolt on weight must be securely mounted and painted white with car number on it
4. No bolt on weight inside driver’s compartment